

FLOW METERS FOR COMPRESSED AIR AND GASES

We measure your air/gas consumption





WELCOME TO FRESH IDEAS

Flow measurement is one of the key factors in any industries to ensure energy efficiency and associated cost reduction to stay ahead of competition.


ENERGY FEEICIENCY

CONSUMPTION MONITORING

LEAK DETECTION

PROCESS EFFICIENCY

COST REDUCTION



Flow meters are our passion, we provide solutions which fits your needs. No matter if you need a compact flow meter for measurements on the spot or an easy to install, long term stable flow meter. A flow meter for wet and dirty air or you need one for explosive and harsh environments.

SUTO iTEC has the right flow meter which fits your needs.

SELECTION TABLE

Application / Medium to measure	Installation Point	Sensor Model	
		Insertion Type	Inline Type
Dry Compressed Air / Dry Gas	Main header	S401	S421
	Point-Of-Use		S415/S418/S421
	Big pipes (>DN65)	S401/S 450	
	Outdoor	S450	S452
	Hazardous environment (ATEX / IECEx)	S450	S452
Wet Compressed Air / Wet Gas		S430	
Vacuum Pumps (Air)			S418-V
Bi-directional Flow Measurement		S401/S430/S450	
Small Flow Rates			S415/S418



S401 / S421

FLOW AND CONSUMPTION SENSOR FOR COMPRESSED AIR AND GASES



Features

Thermal mass flow – measures flow and total consumption

Isolated Analog and Pulse / Modbus/RTU / Modbus/TCP output

Flexible installation under pressure, pipes sizes 1" ... 20"

S421: DN15 ... DN80 and optional flow conditioner

2 Calibration Curves can be saved to the internal memory

S421: Sensor is calibrated in its measuring section

Can be used in almost any technical gas



S450 / S452

FLOW AND CONSUMPTION SENSOR FOR COM-PRESSED AIR AND GASES (ATEX/EX)



Thermal mass flow – measures flow and total consumption

Rugged industrial enclosure for outdoor and hazardous environments

ATEX/IECEx certification as option

Isolated Analog and Pulse / Modbus/RTU / HART output

All parts which are in contact with the medium are stainless steel

S452: Inline version with measuring section DN15 ... DN80

No moving parts – laser welded sensor elements

S452: Measuring sections EN 1092-1 / ANSI-Flange or NPT-/ R-thread







Features

FLOW AND CONSUMPTION SENSOR FOR COMPRESSOR PERFORMANCE TESTS AND FAD-MEASUREMENTS



with SUTO App





Pitot tube principle for wet air application

Insertion type sensor – flexible installation under pressure

No mechanical wear parts

Isolated Analog and Pulse / Modbus/RTU / Modbus/TCP output

Pipe diameters from 1" ... 20"

Compressor-FAD-Measurement







S415

FLOW AND CONSUMPTION SENSOR FOR COMPRESSED AIR AND GASES FOR POINT OF USE APPLICATIONS





Features

Thermal mass flow – measures flow and total consumption

Economic flow sensor for point of use measurement

Isolated Analog and Pulse / Modbus/RTU output

Available in DN8, DN15, DN20 and DN25, G inner thread

Integrated flow conditioner eliminates straight inlet requirements





S418 / S418-V

FLOW AND CONSUMPTION SENSOR FOR COMPRESSED AIR AND VACUUM APPLICATIONS



Thermal mass flow - measures flow, total consumption and pressure

High accuracy

Data logger integrated

S418-V: Calculates actual flow for vacuum pumps

Isolated Analog and Pulse / Modbus/RTU / HART output





Flow measurement is one of the key factors in any industries to ensure energy

efficiency and associated cost reduction to stay ahead of competition.

SUTO ITEC

your partner in measurement

SUPPORT

PARTNERSHIP

RELIABLE

INNOVATIVE

ACCURATE

EUROPEAN OFFICE	CHINA OFFICE	ASIA / PACIFIC OFFICE
SUTO iTEC GmbH	SUTO iTEC (China) Co. Ltd	SUTO iTEC (ASIA) Co. Limited
Grißheimer Weg 21 79423 Heitersheim Germany Tel: +49 (0) 7634 504 88-00 Fax: +49 (0) 7634 504 88-19	D3 Building, Unit A, 11/F, TCL International E City 1001 Zhongshanyuan Road, Nanshan Shenzhen, China Tel: +86 (0) 755 8619 3164	Room 10, 6/F, Block B, Cambridge Plaza 188 San Wan Road, Sheung Shui, N.T. Hong Kong Tel: +852 2328 9782 Fax: +852 2671 3863
Email: sales@suto-itec.com	Fax: +86 (0) 755 8619 3165 Email: sales.cn@suto-itec.asia	Email: sales@suto-itec.asia

